

A NEW ROUTE TO PREPARE GRAPHENE/IRON OXIDE COMPOSITE ELECTRODE FOR BATTERIES.

José Ramón González Jiménez^a, Rosa Menéndez^b, Ekaterina Zecheva^c, Radostina Stoyanova^c, Francisco Nacimiento Cobos^a, Ricardo Alcántara Román^a, Pedro Lavela Cabello^a, José Luis Tirado Coello^a.

^aLaboratorio de Química Inorgánica, Campus de Rabanales, Universidad de Córdoba, 14071 Córdoba (Spain).


^bInstituto Nacional del Carbón (INCAR-CSIC), Apdo. 73, 33080 Oviedo (Spain).

^cInstitute of General and Inorganic Chemistry, Bulgarian Academy of Science, 1113 Sofia (Bulgaria).
e-mail: p22gojj@uco.es

We have recently used high-intensity ultrasonication to prepare a composite material containing graphene and amorphous nanoparticles of FeO(OH).¹ The procedure is particularly useful to achieve the anchoring of very small nanoparticles of iron oxyhydroxide to the graphene layer (Scheme 1). In addition, the ultrasonication treatment enhances the dispersion of the nanoparticles.

Besides lithium,¹ we have observed that this composite is also able to react reversibly with sodium.

These results open a wide range of possibilities to prepare new composite materials for both lithium and sodium batteries.



Scheme 1. Representation of graphene layers with dangling bonds and anchoring of iron ions after high-intensity ultrasonication.

Acknowledgments

The authors are indebted to MEC (MAT2011-22753), *Junta de Andalucía Proyecto de Excelencia FQM-6017* and research group FQM288.

¹ González, J.R.; Menéndez, R.; Alcántara, R.; Nacimiento, F.; Tirado, J.L.; Zchecheva, E.; Stoyanova *Ultrason. Sonochem.* <http://dx.doi.org/10.1016/j.ultsonch.2014.12.001>.